

11000 U.S. PTO
09/808962
03/16/01

	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---

Accordingly, a need exists for improving the input of vapor or steam into the condenser. A need also exists to ~~increase the effectiveness of the~~ heat transfer in the condenser between vapor or steam and the temperature exchanging media.

According to the present invention the optimum function of a condenser during the

process of condensation can be achieved through the use of a controlling device, which is installed on the steam or vapor input line. That controlling device is handled by the pressure controller, which compares the value of the pressure of steam or vapor input to the condenser with the value assigned in the set point adjuster. When the controlling device is opened a portion of the steam or vapor enters into the condenser and the pressure in the steam or vapor input line is reduced. If the controller which compares the value of the pressure of steam or vapor input into the condenser with the value assigned in the set point adjuster registers that the value is equal to the set point, it closes the controlling device. At the same time when the controlling device is closed, the pressure in the steam or vapor input line is increased. If the value of the pressure of steam or vapor in the input line becomes equal to the assigned value in the set point adjuster, the controlling device is opened.

According to the second embodiment of the present invention the temperature controller compares the value of the temperature of condensation in the steam or vapor input line to the temperature in the condenser. When the controlling device is opened, a portion of steam or vapor enters the condenser and the pressure is reduced in the steam or vapor input line of the condenser. The temperature controller compares the temperature of the condenser in a steam or vapor input line to the temperature level assigned in the set point adjuster. If that value is equal to the set point the controlling device is closed. At the same time when the controlling device is closed, the temperature is increased in the steam or vapor input line. If the temperature of the steam or vapor in the input line becomes equal to the temperature level assigned in the set point adjuster, the controlling device is opened.

According to the third embodiment of the present invention the pressure controller compares the value of the pressure of the condensation being drawn off from the condenser with the value assigned at the set point adjuster. A portion of steam or vapor enters the condenser through the open controlling device installed on the steam or vapor input line of the condenser. The pressure is increased in the line drawing off the condensation from the condenser. The pressure controller compares the value of the pressure in the line drawing off the condensation from condenser to the value assigned in the set point adjuster. If that value is equal to the set point, the controlling device is closed. At the same time when the controlling device is closed the pressure is reduced in the line drawing off the condensation from the condenser. If the value of the pressure in the line drawing off the condensation from the condenser becomes equal to the value assigned in the set point adjuster, the controlling device is opened.

According to the fourth embodiment of the present invention the temperature controller compares the temperature of condensation in the line drawing off from the condenser with the temperature level assigned in the set point adjuster. A portion of steam or vapor enters the condenser through the open controlling device installed on the steam or vapor input line of the condenser. The temperature is increased in the line drawing off the condensation from the condenser. The temperature controller compares the temperature in the line drawing off the condensation from the condenser to the value assigned in the set point adjuster. If that value is equal to the set point, the controlling device is closed. At the same time when the controlling device is closed, the temperature is reduced in the line drawing off condensation from the condenser. If the temperature in the line becomes equal to the temperature level assigned in the set point adjuster, the

controlling device is opened.

Due to the interrupted character of the input of vapor or steam into the condenser, the film of condensation on the heat exchanging space is thinner than in existing systems or totally disappears. Therefore, the resistance to the heat transferring process is reduced and the effectiveness is increased. In addition, a deep sub-cooling process of condensation is achieved, so that the energy of steam or vapor is used more efficiently. In the case of condensing vapor of refrigerant, the sub-cooling increases the effectiveness of refrigeration to a significant degree.

The above described and many other features and attendant advantages of the present invention will become apparent as the invention becomes better understood by reference to the following detailed description when considered in conjunction with the accompanying drawing.

DESCRIPTION OF THE DRAWING

A detailed description of the preferred embodiment of the invention will be made with reference to the accompanying drawing.

FIG. 1 shows a condenser unit in accordance with preferred embodiment of the present invention.

FIG. 2 shows a condenser unit in accordance with the second embodiment of the present invention.

FIG. 3 shows a condenser unit in accordance with the third embodiment of the present invention.

FIG. 4 shows a condenser unit in accordance with the fourth embodiment of the present invention.

DETAILED DESCRIPTION OF THE DRAWING

The following is a detailed description of the best presently known mode of carrying out the invention. This description is not being taken in a limiting sense, but is made merely for the purpose of illustrating the general principles of the invention. The scope of the invention is defined by the appended claims.

The condenser 6 (see **FIG.1**) with pipes 5 for the flow of cooling media is connected to steam or vapor input line 1 and discharges the condensation through line 7, a controlling device 2 with set point adjuster is installed on said line 1, a pressure controller 4 is connected to line 1 by link 3 and connected to the controlling device 2. When a portion of steam or vapor enters the condenser 6 through the open controlling device 2, the pressure in steam or vapor input line 1 is reduced. The pressure controller 4 compares the value of the pressure of steam or vapor input to the condenser 6 with the value assigned in the set point adjuster and, if that value is equal to the set point, it closes the controlling device 2. At the same time when the controlling device 2 is closed, the pressure in steam or vapor input line 1 is increased. If the value of the pressure of steam or vapor in said line 1 becomes equal to the value assigned in the set point adjuster, the controlling device 2 is opened.

According to the second embodiment of the present invention the condenser 6 (see **FIG.2**) with pipes 5 for the flow of cooling media is connected to steam or vapor input line 1 and discharges the condensation through line 7, a controlling device 2 with set point adjuster is installed on said line 1, a temperature controller 9 is connected to the line 1 by link 8 and is connected to the controlling device 2. When a portion of steam or vapor enters the condenser 6 through the open controlling device 2, the temperature in

steam or vapor input line 1 is reduced. The temperature controller 9 compares the temperature level of steam or vapor input to the condenser 6 with the value assigned in the set point adjustment and, if the value is equal to the set point, closes the controlling device 2. At the same time when the controlling device 2 is closed, the temperature in said steam or vapor input line 1 is increased. If the value of the temperature of steam or vapor in said line 1 becomes equal to the value assigned in the set point adjustment, the controlling device 2 is opened.

According to the third embodiment of the present invention the condenser 6 (see **FIG.3**) with pipes 5 for the flow of cooling media is connected to steam or vapor input line 1 and discharges the condensation through line 7, a controlling device 2 with set point adjuster is installed on said line 1, a pressure controller 4 is connected to line 7 by link 10 and connected to the controlling device 2. When a portion of steam or vapor enters the condenser 6 through the open controlling device 2, the pressure in steam or vapor input line 1 is reduced. The pressure controller 4 compares the value of the pressure of condensation discharged from the condenser 6 with the value assigned in the set point adjuster and, if that value is equal to the set point, closes the controlling device 2. At the same time when the controlling device 2 is closed, the pressure in line 7 is reduced and the condensation from the condenser 6 is discharged off. If the value of the pressure of the condensation in said line 7 becomes equal to the value assigned in the set point adjuster, the controlling device 2 is opened.

According to the fourth embodiment of the present invention the condenser 6 (see **FIG.4**) with pipes 5 for the flow of cooling media is connected to line 1 and discharges the condensation through line 7, a controlling device 2 with set point adjuster is installed